



Information to Users

<p>CE These garments comply with the requirements of Directive 89/686/EEC and the referenced standards</p>	<p>STYLE REFERENCE: AC205-000-282 AC210-000-036 AC211-000-282 AP009-000-036 AP010-000-036 GL143-000-036 JK941-000-036</p>	<p>DESCRIPTION: FLAME RETARDENT WELDERS GAITERS IN TAN / GREY FLAME RETARDENT WELDERS GAITERS(TAN) FLAME RETARDENT WELDERS GAITERS(TAN) VELCRO FASTENING FLAME RETARDENT WELDERS APRON (TAN) FLAME RETARDENT WELDERS SHORT APRON FLAME RETARDENT WEDERS RAGLAN SLEEVE (TAN) FLAME RETARDENT WELDERS BOLERO(TAN)</p>
<p>EN ISO 11611:2007 Protective Clothing for use in Welding and Allied Processes</p>		 <p>EN ISO 11611 2007 CLASS 2 A1</p>
<p>In the event of accidental splash of Chemicals or Flammable liquids on clothing the Wearer should withdraw and carefully remove garments, ensuring the chemical or liquid do not come into contact with any part of skin. Clothing should be cleaned or removed from service.</p>		<p>Intended Use: Class 1 – recommended for manual welding techniques with light formation of Spatters and drops e.g. gas welding, TIG-welding, MIG welding, micro plasma welding, brazing, spot welding, MIMA welding (with rutile covered electrode) for operation of machine e.g. oxygen cutting machines, plasma cutting machines, resistance welding machines, machines for thermal spraying, bench welding</p>
<p>Improper use. The level of protection against flame will be reduced if the welders' protective clothing is contaminated with flammable materials. An increase in the oxygen content of the air will reduce considerably the protection of the welder's protective clothing against flame. Care should e.g. taken when welding in confined spaces e.g. if it is possible that the atmosphere may become enriched with oxygen. The electrical insulation provided by clothing will be reduced when the clothing is wet, dirty or soaked with sweat. Any other warnings, regarding limitations of use, as identified by the manufacturer.</p>		<p>Class 2 – recommended for manual welding techniques with heavy formation of spatters and drops e.g. MIMA welding (with basic or cellulose-covered electrode), MAG welding (with CO₂ or mixed gases), MID welding (with high current), self-shielded flux cored arc welding, plasma cutting, gouging, oxygen cutting, thermal spraying for operation of machines e.g. in confined spaces, at overhead welding/cutting or in comparable constrained positions</p> <p>This clothing is intended to protect against flames molten metal spatter, radiant heat and short term, accidental electrical contact</p> <p>Warnings: For operational reasons not all welding voltages carrying parts of arc welding installations can be protected against direct contact.</p>
<p>Cleaning & Maintenance; The items of PPE described and marked with the appropriate style/ product codes are not designed to be Washed, Laundered or Cleaned in any manner.</p>		<p>DO NOT WASH</p> 
<p>Notified Body : Intertek Labtest UK Ltd Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK Notified Body No.0362</p>		<p>Aprons should cover the front body of the user at least from side To side seam Additional partial body protection may be required e.g. for welding overhead.</p>
<p>FUTURE GARMENTS LTD. AQUA HOUSE, BUTTRESS WAY, SMETHWICK, BIRMINGHAM, WEST MIDLANDS, B66 3DL, UK www.workwearonline.net</p>		<p>This garment is only intended to protect against brief inadvertent contact with live parts of an arc welding circuit, additional electrical insulations layers will be required where there is an increased risk of electric shock. Garments are designed to provide protection against short term, accidental contact with live electric conductors at voltages up to approximately 100 V.d.c. Garments should fastened and worn correctly for protection. When using additional partial protective garments, the basic garments shall meet at least Class 1. Storage: Always store in clean, dry conditions. Disposal: Products for recycling, safe destruction and disposal as relevant with local regulations</p>