

XPERT GCM 3500 CNC Plasma System



Xpert GCM 3500 is a robust gantry designed for superior cutting performance through smooth motion and accuracy for medium thickness plates of mild steel, stainless steel and aluminium. Its dual-side, high-speed AC drives and high-speed plasma lifter helps deliver high productivity.

- Quick Set-up with Split screen for next job preparation while viewing current job
- Integrated Promotion Software & Cut Cost Calculator
- Remote Diagnostics
- **PERFORMANCE:** A dual-drive system that produces higher-quality cutting parts as a result of high speed and smooth motion.
- **PRODUCTIVITY:** Technological innovation and automation of the entire process produces the highest productivity in any application.
- **SAFETY :** Anti-collision system protects the plasma torch from damage during collision.



Xpert GCM 3500 Gantry

Features:

- Windows 10 Embedded OS
- Quad Core Intel Processor for motion & I/O
- 250 GB SATA SSD Hard drive
- In-built Wi-Fi
- Auto-logging of Cutting Statistics
- In-built Nesting Software
- Automatic machine software back-up
- Remote diagnostics



Simple CNC with easy menu-driven operation

Industries:

- Light fabricación
- Industrial & General fabrication
- General manufacturing
- Structural steel fabrication



High Cut Quality

XPERT GCM 3500

CNC Plasma System

| Specifications of machine | |
|---------------------------------|----------------------|
| Input Power | 3 phase 415V 50/60HZ |
| Effective Cutting Width | 3,000 mm |
| Effective Cutting Length | 6,300 mm / 13,000 mm |
| Output current range | 30 - 120A |
| Plasma Torch | SL 100 |
| Plasma System | ESAB PC-120 |
| Plasma Cutting Range | 3 – 16 mm |
| CNC | iCNC Performance-e |
| Positioning Speed | Maximum 12000 mm/min |
| Recommended Cutting Speed Range | 3,000 – 6,000 mm/min |
| Positioning Accuracy | 0.5 / 1000 mm |
| Positioning Repeatability | 0.2 / 1000 mm |

| Specifications of ESAB PC 120 | |
|-------------------------------|-------------------------|
| Max output | 120 A |
| Recommended cut | 16 mm |
| Mains supply, 50/60 Hz | 415 VAC, 3 Phase supply |
| Output range | 30 - 120A |
| Output power | 15.4 Kw |
| Output at 80% duty cycle | 120 A |
| Output at 100% duty cycle | 100A @40°C |
| Max OCV | 260 VDC |
| Torch air pressure | 4 bar – 6 bar |
| Torch air consumption | 189 l/min (400.5 cfh) |
| Weight, incl cable and torch | 52 kg (115 lbs.) |

| Ordering Information | |
|--------------------------------------|-------------|
| Description | Part number |
| Xpert GCM 3500 X 8000/PC120/Oxy fuel | 4660102000 |
| Xpert GCM 3500X 15000/PC120/Oxy fuel | 4660102001 |



ESAB / esab.com

